

The HD21N Hybrid (IP Streaming, USB & Digital Output) PTZ camera is equipped with a professional SONY 1/2.8" Progressive CMOS with 2.1 megapixels output resolution that delivers a clear and vivid live image



## Features:

- Effective Pixels: 1/2.8" SONY CMOS, 1080P 2.1 Megapixels
- Zoom: 20X Optical Zoom f=4.7~94mm
- Simultaneous 1080P video output interfaces: HDMI, 3G-SDI, POE IP & USB
- Multiple Video Formats Output: 1080p60/50, 1080p30/25, 1080i60/50, 720p60/50
- Multiple Video compression: H.265/H.264 & MJPEG video compression
- Multiple Network Protocol Support ONVIF, RTSP, RTMP and RTMPS push mode (direct streaming to media services: Facebook Live & YouTube)
- 255 Preset Positions
- Supports VISCA, Pelco-D, & Pelco-P
- Adopt 2D and 3D DNR Motion Estimation Algorithm, Low Noise CMOS Sensor
- Quiet Motor, Servo Algorithm for PTZ Control, Precise location( $\pm 0.01^\circ$ )
- Horizontal Speed: 0.1-100°/s; Vertical Speed: 0.1-90°/s
- 340° Horizontal Angle; 120° Vertical Angle
- Remote Control: IR, IP Web Browser, RS-422/RS-485 Control
- IR Transparent Transmission: Able to Receive the Video Conference Terminal's IR Control Signal
- Firmware Update via Web Browser
- Desktop or Inverted Ceiling Mountable, Wall Mount Bracket (included)
- Supports POE power (802.3af <15 Watts) and includes 12v 2amp Power Supply